

Vulkacit[®] Thiuram/C**Product Description**

tetramethyl thiuram disulphide (TMTD)

Supply Form

white to greyish powder, low dust

Product Characteristics

Property	Nominal Value	Unit	Test Method
Melting point (heating rate: 3 °C/min)	≥ 142.0	°C	ASTM D 1519 B
Assay	≥ 96.0	%	2011-0364501-92
Ash content	≤ 0.3	%	ASTM D 4574
Volatile matter	≤ 0.3	%	ASTM D 4571 (15 - 23)
Oil content	2.0 ± 1.0	%	32 A
Sieve residue (0.063 mm)	≤ 0.3	%	ASTM D 4572

Vulkacit[®] Thiuram/C**Other Product Features**

Property	Typical Value
Density	1.3 g/cm ³
Packaging	20 kg paper bags stacked on pallets
Storage Life/Conditions	2 years from date of production, keep cool (approximately 25 °C) and dry in closed original packaging
Product Safety	Relevant safety data and references as well as any necessary warning labels are to be found in the EU safety data sheet MSDS-Number: 077007

These raw material properties are typical and, unless specifically indicated otherwise, are not to be considered as delivery specification.

Vulkacit is a Registered Trademark of Bayer AG

Issue number: 05 / Date of issue: December 09, 2004 / Previous issue from December 2000

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.