

LEVAPREN[®] 800 XL VP**Grade Name**LEVAPREN[®] 800 XL VP**Product Description**

Ethylene-vinyl acetate copolymer (EVM, precrosslinked) with 80 wt % vinyl acetate and dusted with separating agents (silica and talc).

Supply Form

Granules, almost colorless

Production Site

Dormagen, Germany

Specifications¹

Characteristics	Limits	Unit	Testing Method	Condition
Mooney Viscosity	55 ± 10	MU	ISO 289/ASTM D 1646	UML(1+4) 100 °C, unmassed
Volatile Matter	≤ 0.6	wt%	ISO 248/ASTM D 5668	105 °C, 6h
Vinyl acetate content	80 ± 2	wt%	Internal Method LP 015	(VAC)
Total Ash	≤ 0.8	wt%	According to ISO 247/ASTM 5667	10min at 800 °C

¹For each delivery a Certificate of Analysis (CoA) will be sent, which contains the actual measured values of the specified properties for each batch.

Typical Product Features²

Characteristics	Limits	Unit	Testing Method	Condition
Density	≈ 1.07	g/cm ³	INN PV 476	

²Not to be considered as delivery specification.



LEVAPREN[®] 800 XL VP

Identification

The bags are marked with the Levapren[®] Grade name, lot number and single bag number. Additional cardboard boxes are marked with the Levapren[®] Grade name only. The pallets/boxes are marked with the producer name and address, product name, lot number and net weight. All pallets/boxes are marked with a unique 20-digit code (Stock Unit Number) for traceability.

Packaging

The material is filled in 25 kg polyethene bags, packaged in cardboard boxes and delivered on a wooden pallet containing 30 boxes (net weight per pallet 750 kg) covered by a PE stretching film.

Storage Conditions

Store under moderate temperatures and dry conditions in original packaging. Avoid exposure to the light. Do not stack pallets/boxes at storage. The temperature for storage shall not exceed +40 °C and only if flowability of the Granules is no keyfactor. Keep storage to a minimum. Granules tends to block at temperatures above +25 °C or if stored improperly. For this reason, the flowability of this product is explicitly not warranted. If flowability is an important keyfactor for your process, ask your ARLANXEO customer contact for other product solutions.

Shelf Life

36 month from date of production (see CoA) warranted under the above mentioned storage conditions. The expiration of the best before date does not necessarily mean that the product has become unusable. However, before using such a product, it is necessary that the customer check the product as to whether the Specifications of the product are still present. ARLANXEO does not assume a warranty or liability for compliance with the Specifications after Expiration of the best before date.

Delivery Conditions

Please find our General Conditions of Sale & Delivery at our website www.ARLANXEO.com

Document Validity

This product specification becomes valid with the signature of ARLANXEO and is valid until the next update. Customers will be informed as soon as reasonably practical about changes with regards to the process, to manufacturing plant, to testing methods, etc. which, to the best of our knowledge, may affect the specified properties.

Contact

In case of technical questions, please get in contact with our Technical Support via the known communication channels.



LEVAPREN[®] 800 XL VP

Date / Issue

Issue number: ARL 02 / Date of issue: March 03, 2017 / Previous issue from October 07, 2016 / Information current as of date of issue. Please contact your ARLANXEO representative to determine if this publication has been revised.

Signature

ARLANXEO USA LLC
via ARLANXEO Deutschland GmbH
BU High Performance Elastomers
Global HSEQ
Quality Management & Product Stewardship
i.V.



LEVAPREN[®] (EVM) is a Registered Trademark of Bayer AG, Germany

Developmental/Trial Product:

Developmental/Trial products (noted as such or designated by the letters VP in the product code) are not considered part of the ARLANXEO Corporation line of standard commercial products. Complete commercialization and continued supply are not assured. The purchaser/user agrees that ARLANXEO Corporation reserves the right to discontinue this product without prior notice.

Health and Safety Information: Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the ARLANXEO products mentioned in this publication. For materials mentioned which are not ARLANXEO products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use, and handling. This cannot be overemphasized. Information is available in several forms, e.g., *material safety data sheets and product labels*. Consult your ARLANXEO Corporation representative or contact the Product Safety and Regulatory Affairs Department at ARLANXEO.

ARLANXEO Corporation

111 RIDC Park West Drive · Pittsburgh, PA 15275 · Phone: 1-800-526-9377 ARLANXEO · www.US.ARLANXEO.com

